

5

REPAIR OF LINED PIPES

10

FIELD OF THE INVENTION

This invention relates to a method of refurbishing a lined pipeline and means to facilitate such refurbishment.

15

- 5 Throughout this specification the term "lining composition" shall be taken as including any form of composition such as cement mortar, concrete, plastics materials (such as urethane or ethylene based materials), epoxy materials, paints or like compositions which are suitable for application to the internal surface of a pipeline for use as a protective lining.

20

25

10 BACKGROUND

A particular application of the invention relates to the refurbishing of water pipelines which have been lined with a lining composition.

30

In regard to water pipelines it has been conventional practice to provide the pipelines with a cement lining in order to protect the internal face of the pipeline from corrosion. However, a significant difficulty arises with lined water pipelines when the lining deteriorates and the protection which is offered by the lining is reduced. In the past, in circumstances where the lining has become degraded or damaged, it has been conventional practice to remove from the pipeline the damaged length of pipeline and replace it by a section of new pipeline or alternatively to completely remove all of the existing lining and replace it with a fresh lining or alternatively patch repair the localised lining failure manually. Each of these exercises has proven to be unnecessarily expensive exercises.

35

40

- 20 Alternatively to completely remove all of the existing lining and replace it with a fresh lining or alternatively patch repair the localised lining failure manually.

45

However, it has been found that the existence of minor cracks or like physical damage to the lining need not necessarily be indicative that the lining is failing to provide its protection action since it has been found that the alkaline environment provided by the lining seems to provide a protective environment for the inner

50

55

5 face of the pipeline. Furthermore, even after the chemical protection has been
lost, the presence of a physical barrier which is provided by the degraded lining
10 seems to delay the progress of corrosion of the pipe. Therefore it is only when
the lining of the pipeline has been degraded such that it is unable to provide the
5 desired chemical and physical protection of the pipeline that it becomes
necessary to replace the lining. In addition it has been found that the
15 degradation does not usually occur uniformly but is only localised at particular
locations in the lining (even in pipelines of considerable age) and the degree of
localisation of the damage or deterioration does not warrant the wholesale
20 replacement of a length of pipeline or the wholesale refurbishment of the lining of
the pipeline. Therefore the wholesale replacement of pipe or the lining can in
many cases be unnecessary and extremely wasteful.

25 It is an object of this invention to provide a means and a method whereby the
cement lining of a pipeline can be selectively refurbished as required where such
15 refurbishment can comprise the complete replacement of large sections of lining
and/or partial refurbishment of patches of lining.

30 DISCLOSURE OF THE INVENTION

35 Accordingly the invention resides in a method of selectively repairing the lining of
a lined pipeline, said method comprising utilisation of a conveyance adapted to
20 be receivable within the pipeline, said conveyance being adapted to be able to
travel through the pipeline, said method further comprising introducing said
40 conveyance into the pipeline, said conveyance comprising an inspection means,
an excising means, a debris removal means and an application means, said
method further comprising an identification step comprising causing the
45 conveyance to travel along the length of the pipeline, inspecting the surface of
the lining and identifying and locating damaged portions of the lining at locations
along the pipeline, said method further comprising an excising step comprising
moving said conveyance means along the pipeline and at the locations identified
50 by the inspection excising the damaged portions of the lining from the pipeline,
30 said method further comprising a debris removal step comprising causing said

5 conveyance means to travel along said length of the pipeline to remove the
debris left in the pipeline by the excising step, and said method comprising an
10 application step comprising causing said conveyance means to travel along the
said length of the pipeline and applying a fresh lining composition onto the lining
5 to replace the excised portions of lining removed by the excising step.

15 According to a preferred feature of the invention said method further comprises
cutting a length of pipe from the pipeline at a location to provide a gap in the
pipeline at the location, locating a support tray between the opposed ends of the
remaining pipeline to span the lower portion of the gap and to provide a
20 continuation of the lower surface of the pipeline across the gap. According to a
particular embodiment of the invention the pipeline is above the ground at the
location. According to an alternative form of the invention the pipeline is buried
25 at the location and the method further comprises exposing the length of pipe at
the location prior to the length of pipe being cut from the pipeline.

15 According to a preferred feature of the invention said conveyance means
30 comprises a plurality of self propelled and self powered vehicles which comprise:
at least one inspection vehicle for said inspection step; an excising vehicle for
said excising step; at least one removal vehicle for said removal of debris step;
35 and at least one application vehicle for said application step.

20 According to a preferred feature of the previous feature of the invention at least
some of the vehicles are adapted to be operated remotely. According to one
40 embodiment all of the vehicles are adapted to be operated remotely. According
to an alternative embodiment at least one of the vehicles is adapted to be
operated by an operator in-situ in the pipeline and incorporates controls operable
25 by the operator to effect at least some of the operations of the vehicle. According
to a feature of the alternative embodiment the at least one vehicle is provided
with a support to enable the operator to be supported by the vehicle. According
45 to an alternative feature of the embodiment the at least one vehicle is associated
with an operator trolley which is coupled to the at least one vehicle wherein the
50 operator trolley is provided with a support to enable the operator to be supported
30

5 by the operator trolley. According to a particular form the operator trolley is provided with the controls.

10 According to a preferred feature of the invention said inspection step comprises causing the inspection vehicle to travel along the interior of the pipeline and
5 during such travel inspecting the lining within the pipeline, identifying locations of damaged or deteriorated lining and maintaining a log recording the axial position
15 of said location along the length of the pipeline, the radial location of the location around the pipeline, and the type of damage. According to one embodiment of the invention the inspection step is conducted remotely. According to an
20 10 alternative embodiment the inspection step involves utilisation of an operator supported on the inspection vehicle, said operator being skilled in identifying the damaged or deteriorated portions of the lining, said identifying of damaged or deteriorated lining including the operator providing markings on the lining to
25 indicate the locations.

15 According to a further preferred feature of the invention said excising step comprises utilisation of a remotely controlled nozzle connected to a source of
30 high pressure fluid whereby said nozzle is able to be moved to direct a jet of said high pressure fluid, said remotely controlled nozzle being supported from the excising vehicle, said method causing the excising vehicle to travel along the
35 20 interior of the pipeline and during such travel causing the nozzle to direct said jet of said high pressure fluid onto the damaged lining at the locations in order to remove the lining at said locations. According to one embodiment the excising vehicle is associated with a remote control station which is provided with a
40 display means and controls to enable the remote operation of the vehicle and the
25 nozzle from the control station by an operator.

45 According to a further preferred feature of the invention said debris removal step comprises causing a removal vehicle to travel along the interior of the pipeline and causing the removal vehicle to collect debris from the interior of the pipeline
50 as it travels. According to one embodiment the removal step initially comprises
30 causing a primary removal vehicle to travel along the interior of the pipeline,

5 scooping large items from the pipeline as it travels along the pipeline and
conveying the items into a hopper associated with the primary removal vehicle.
10 According to a further preferred feature of the embodiment said debris removal
step further comprises causing a secondary removal vehicle to travel along the
5 interior of the pipeline and causing the secondary removal vehicle to brush the
surface of the pipeline to extract smaller items of debris from the pipeline.
15 According to a further preferred feature of the embodiment said debris removal
step further comprises causing a tertiary removal vehicle to travel along the
interior of the pipeline and causing the tertiary removal vehicle to wash and
20 vacuum fine debris and water from the pipeline.

According to a preferred feature of the invention said application step comprises
causing the application vehicle to travel along the length of the pipeline and
causing the application vehicle to applying the fresh lining composition to the
25 locations at which the lining has been excised. According to one particular
15 embodiment the lining composition is applied to a discrete location by spraying
utilising a directional nozzle. According to an alternative embodiment the lining
composition is applied around the internal circumference of the pipeline by the
centrifugal application of the lining composition. According to a preferred feature
30 of the embodiments the lining composition comprises a cementitious composition.

35 20 According to a preferred feature of the invention the method further comprises the
delivery of lining composition to the application vehicle during the application of
the lining composition to the pipeline. According to one embodiment the lining
40 composition is delivered to the application vehicle by a delivery vehicle which is
adapted to be able to travel through the pipeline and carry a quantity of lining
25 composition to the application vehicle, said delivery vehicle having a conveying
means adapted to be able to convey the lining composition from the delivery
45 vehicle to the application vehicle.

50 Accordingly the invention also resides in a conveyance for use in the selective
refurbishment of the internal cement lining of a pipeline according to the method
30 described above, said conveyance comprising a plurality of vehicles capable of

5 independently travelling along the pipeline for the purposes of inspection,
excising damaged lining, removal of debris and application of a fresh lining
10 composition, each of said vehicles being configured such that their centre of
gravity when in use is below the central longitudinal axis of the pipeline and each
5 of said vehicles being self powered and self propelled.

15 According to a preferred feature of the invention said conveyance means
comprises a plurality of self propelled and self powered vehicles which comprise:
an inspection vehicle for said inspection step; an excising vehicle for said
excising step; at least one removal vehicle for said removal of debris step; and at
20 10 least one application vehicle for said application step.

25 According to a preferred feature of the previous feature of the invention at least
some of the vehicles are adapted to be operated remotely. According to one
embodiment all of the vehicles are adapted to be operated remotely. According
to an alternative embodiment at least one of the vehicles is adapted to be
15 operated by an operator in-situ in the pipeline and incorporates controls operable
by the operator to effect at least some of the operations of the vehicle. According
30 to a feature of the alternative embodiment the at least one vehicle is provided
with a support to enable the operator to be supported by the vehicle. According
35 to an alternative feature of the embodiment the at least one vehicle is associated
20 with an operator vehicle which is coupled to the at least one vehicle wherein the
operator vehicle is provided with a support to enable the operator to be supported
by the operator vehicle. According to a particular form the operator vehicle is
40 provided with the controls.

45 According to a preferred form the inspection vehicle incorporates a viewing
25 means which comprises an illumination means and a viewing means comprising
at least one camera adapted to facilitate inspection of the lining of the pipeline
remotely.

50 According to a further preferred feature of the invention the excising vehicle
accommodates a nozzle which is supported to be capable of rotation about a
55

5 longitudinal axis of said pipeline whereby said nozzle is adapted to be able to
direct a stream of high pressured fluid onto the lining to remove the lining from
the pipe interior. According to an embodiment of the invention the excising
10 vehicle is associated with an umbilical incorporating a delivery conduit for said
5 high pressure fluid. According to a further preferred feature of the invention the
excising vehicle further comprises an illumination means and a viewing means
15 comprising at least one camera to facilitate remote inspection of the location
being subjected to the action of said stream of high pressure fluid. According to
one preferred feature the high pressure stream of fluid incorporates abrasive
20 particles. According to a further preferred feature of the invention the orientation
of the stream to the surface of the pipeline can be adjusted. According to a
further preferred feature of the previous feature the excising vehicle incorporates
a second nozzle which is directed onto the lower portion of the pipeline forward of
25 the vehicle, wherein the second nozzle generates a forwardly directed jet of fluid
15 having a transverse extent.

According to a further preferred feature of the invention the debris removal
30 vehicle is adapted to travel along the pipeline and collect the debris generated by
the excising step from the pipeline wherein the vehicle is adapted to remove large
and small items of debris from the pipeline. According to a preferred feature of
35 the invention the debris removal vehicle comprises a plurality of vehicles
comprising a primary vehicle adapted to remove the large items of debris from the
pipeline and a secondary vehicle for removal of the smaller items from the
40 pipeline. According to a particular embodiment the debris removal vehicle also
comprises a tertiary vehicle for the removal of fine material from the pipeline.
25 According to one embodiment the primary vehicle comprises a scooping means,
a conveying means and a hopper said scooping means being adapted to scoop
larger items of debris from the pipeline, the conveying means being adapted to
45 convey the items from the scooping means to the hopper. According to the
embodiment the secondary vehicle comprises a brushing means, a vacuum
30 extraction means and a hopper, said brushing means being adapted to brush the
lower surface of the pipeline, the vacuum extraction means being adapted to

- 5 convey the fine materials and water to the hopper. According to the embodiment
the tertiary vehicle comprises a washing means, a vacuum extraction means and
a hopper, said washing means being adapted wash the fine materials from the
10 the surface of the pipeline, the vacuum extraction means being adapted to convey
5 the fine materials and water to the hopper. According to an alternative
embodiment the debris removal vehicle comprises a single vehicle incorporating
scooping means, a brushing means, a washing means, a conveying means, a
15 vacuum extraction means and a hopper, said scooping means being adapted to
scoop larger items of debris from the pipeline, the conveying means adapted to
10 convey the items to the hopper, the brushing means adapted to brush the lower
20 surface of the pipeline, the washing means adapted to wash fine materials from
the surface of the pipeline, the vacuum extraction means associated with the
brushing means and washing means to convey materials dislodged by the
25 brushing means and the washing means to the hopper.
- 15 According to a further preferred feature of the invention the application vehicle
comprises a hopper adapted to accommodate a quantity of said lining
30 composition, a pump means for pumping said lining composition and an outlet
which is capable of directing said lining composition onto the surface of the
pipeline. According to one embodiment a delivery means is provided between
35 20 the hopper and the pump and the delivery means is adapted to deliver the lining
composition to the pump. According to one embodiment the application vehicle
includes an operator trolley which is adapted to accommodate an operator,
wherein said outlet is supported from an operator trolley and is adapted to be
40 controlled by the operator. According to a preferred embodiment of the invention
25 the application vehicle is associated with a delivery vehicle having a hopper and
a conveying means whereby said delivery vehicle can be brought into abutting
45 relationship with the application vehicle whereby the conveying means can
deliver lining composition from the hopper of the delivery vehicle to the hopper of
the application vehicle.
- 50 30 According to a preferred feature of the invention the inspection vehicle and
excising vehicle comprise a single vehicle.

5 The invention will be more fully understood in the light of the following description of several specific embodiments.

10 **BRIEF DESCRIPTION OF THE DRAWINGS**

The description will be more fully understood in the light of the following drawings of which;

15 Figure 1 is schematic side elevation of an above ground pipeline which has been prepared for the refurbishment procedure according to the first embodiment;

20 Figure 2 is a schematic side elevation of the inspection vehicle according to the first embodiment;

25 10 Figure 3 is a schematic side elevation of the excising vehicle according to the first embodiment;

30 Figure 4 is a side elevation of the primary removal vehicle according to the first embodiment;

35 15 Figure 5 is a side elevation of the secondary removal vehicle according to the first embodiment;

40 Figure 6 is a side elevation of the tertiary removal according to the first embodiment;

Figure 7 is a schematic side elevation of an application vehicle according to the first embodiment; and

45 20 Figure 8 is a side elevation of a delivery vehicle according to the first embodiment.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

The first embodiment is directed to the refurbishment of an above ground lined water pipeline. The embodiment has particular application to a pipeline which has an internal lining formed of a cementitious composition.

- It is an object of the embodiment to provide a means whereby the damaged portions of the lining of a water pipeline can be selectively replaced as required.

The method according to the embodiment comprises initially cutting a section from the length of pipeline as shown at Figure 1 to create a gap 10 between two opposed ends of the pipeline. In practice it has been found appropriate to create a number of gaps 10 of the form as described above and shown at Figure 1, at spacings of approximately three to four hundred metres apart, whereby the various stages of the refurbishment process (ie. inspection, excising, removal of debris and application) can be effected simultaneously at different locations along the pipeline.

- The gap is filled by a tray 11 which is intended to provide a continuation of the lower portion of the pipeline between the exposed ends 12 of the pipeline which have been created by the creation of the gap. The tray is adapted at each end to be supported from each end 12 of the pipeline. In addition the tray is provided at an intermediate position along its length with an opening in its lower face. Once the tray 11 has been located in position across the gap defined between the two ends of the pipeline a conveyance is then used for the purposes of inspection of the lining of the pipeline, excising damaged portions of the lining, removal of the debris generated by the excising process and application of fresh lining to the excised portions. The conveyance comprises a number of separate vehicles which are capable of travelling along the length of the pipeline. As a result of the creation of a number of gaps 10 the vehicles are only required to travel the length of the pipeline between the adjacent gaps.

The vehicles which comprise the conveyance of the embodiment comprise:

an inspection vehicle 30 (shown at Figure 2);

an excising vehicle 40 (shown at Figure 3);

a primary removal vehicle 50 (shown at Figure 4);

a secondary removal vehicle 60 (shown at Figure 5);

a tertiary removal vehicle 70 (shown at Figure 6);

an application vehicle comprising an operator trolley 80 a hopper vehicle 90 and a battery vehicle 84 (shown at Figure 7); and

a delivery vehicle 100 (shown at Figure 8).

Each of the vehicles comprise a lower chassis which is provided with a set of wheels. In addition each of the vehicles are configured such that the centre of gravity of the vehicle, when in use (including conditions when they accommodate an occupant and/or are carrying a load), is lower than the central longitudinal axis of the pipeline. It is by this location of the centre of gravity that the vehicles are prevented from spiralling around the walls of the pipeline and will remain in the lower portion of the pipeline.

In addition each of the vehicles are movable independently along the length of the pipeline and are independently powered and as a result they do not require utilisation of an external power source in order to effect the movement along the pipeline. This is effected by each vehicle having a set of driven wheels which are driven from electric motors which are operated from a control means which may be remote from the vehicle and/or may be provided on the vehicle. According to the embodiment the front wheels of a vehicle are driven from one electric motor while the rear wheels are driven from another electric motor. The power for each of the drive motors is derived from a battery pack which can be supported from the vehicle. If desired the battery pack may be carried by a separate vehicle (ie

5 battery vehicles 52 of Figure 4, 62 of Figure 5, 72 of Figure 6 and 84 of Figure 7)
where there is insufficient space available on a particular functioning vehicle or it
10 is inappropriate to locate the battery pack on a functioning vehicle given the
function of the functioning vehicle.

5 In some instances the vehicle may comprise or incorporate an operator trolley
15 which is supported from a set of non-driven wheels and has a chassis which is
configured to provide a platform which will accommodate an operator. In each
case the operator trolley is coupled to a the respective functional vehicle which
20 has a chassis which is supported by a set of driven wheels which are associated
10 with drive motors which are drivingly connected to the drive wheels. The
functional vehicle provides the motive force to enable the operator trolley to travel
through the pipeline as well as all specialist equipment to meet the functional
25 requirements of the respective vehicle. In each case the operator trolley is
provide with the appropriate controls to enable the operator to control the
15 movement of the operator trolley through the pipeline and the functions of the
vehicle with which the trolley is associated. In some instances the operator
30 trolley may be provided with a visual display unit screen, an illumination means
and a viewing means in the form of one or more cameras to facilitate the control
of the vehicle with which the operator trolley is associated.

35 20 The method according to the embodiment initially comprises inspecting the length
of pipeline between adjacent gaps 10 in the pipeline. This is effected by
40 utilisation of an inspection vehicle 30 as shown at Figure 2 which comprises an
operator trolley 20, which is supported from a set of non-driven wheels 21 and
has a chassis which is configured to provide a platform which will accommodate
25 an operator 31. The operator trolley is coupled to a traction trolley 32 which has
a chassis which supports a battery pack and is supported by a set of drive wheels
45 35 which are associated with drive motors 34 which are drivingly connected to the
drive wheels 35. The traction trolley 32 provides the motive force to enable the
inspection vehicle to travel through the pipeline. The forward end of the operator
50 30 trolley is provided with a hand control 36 which can be manipulated by the
operator 31 to effect the controlled movement of the inspection vehicle along the

5 pipeline. In addition the operator trolley 30 is associated with an illumination
means which is able to illuminate the walls of the pipeline to facilitate the visual
inspection of the pipeline by the occupant 31. In addition the operator trolley is
10 associated with a communication means. If desired the inspection vehicle can
5 include a viewing means in the form of one or more video cameras which can be
used to provide a record of the state of the pipeline prior to its refurbishment. In
addition according to the embodiment the operator 31 when inspecting the
15 pipeline will physically mark the locations of the damaged portions of the pipeline
for later identification during the excising operation.

20 10 Once the length of pipeline between two adjacent gaps 10 has been inspected
and the damage or degradation to the lining at the various locations along the
pipeline have been identified and marked it is then necessary to excise from the
lining the damaged or degraded portions of the lining at each location. This is
25 effected by utilisation of an excising vehicle as shown at Figure 3. The excising
15 vehicle is operated remotely such that is able to move independently along the
length of the pipeline and as shown at Figure 3 accommodates a battery pack 41
and a set of drive motors 42 which are drivingly connected to the wheels 43 of the
vehicle 40. In addition the forward end of the vehicle 40 is provided with an
illumination means in the form of suitable lights and a set of video cameras which
35 are accommodated within a housing 44 and which facilitate the visual inspection
of the lining in order to control, monitor and record the excising step. In addition
the forward end of the excising vehicle accommodates a excising nozzle 45 which
is capable of rotating about a longitudinal axis of the vehicle and which is
40 directed generally radially. The excising nozzle 45 is intended to effect the
25 removal of the lining at the locations identified by the inspection step and is
capable of producing a jet of high pressure fluid which if desired can incorporate
abrasive particulate materials to enhance its action. In addition the excising
vehicle is provided with a washing nozzle 46 which is directed forwardly and
axially from the forward end of the excising vehicle 40 and which can be adjusted
30 to be directed obliquely at the surface of the pipeline. The washing nozzle 46
produces a spray which is capable of washing the surface of the pipeline. The

5 forward end of the excising vehicle 40 also accommodates a plurality of debris
clearance nozzles 47 which are directed forwardly and downwardly such that it
they are directed onto the surface of the pipeline ahead of the excising vehicle.
10 The debris clearance nozzles 47 jointly produce a high pressure spray having a
5 lateral dimension such that it is able to impact upon debris generated by the
excising process and drive it forwardly of the excising vehicle as the excising
vehicle moves along the length of the pipeline.
15

The excising vehicle 40 is associated with a high pressure fluid delivery conduit
for the delivery of fluid to the excising nozzle 45, the washing nozzle 46 and the
20 debris clearance nozzles 47. The excising vehicle 40 is also associated with an
10 umbilical which accommodates electrical cables for controlling all of the functions
of the excising vehicle and transmitting the signals from the camera and any
other sensors associated with the vehicle to the control room.
25

In use the excising vehicle is caused to travel along the pipeline and when it
15 reaches a previously identified location of damaged lining, the excising nozzle 45
is moved to a position such that it is directed towards the damaged portion and a
30 jet of high stream fluid is then directed towards the damaged portion in order to
remove the damaged portion of lining. During this operation the action of the
excising nozzle 45 can be monitored through the camera to ensure that the
35 excising action is adequate. In addition as the excising vehicle 40 moves along
20 the length of the pipeline the surface of the pipeline is washed by the washing
nozzle 46 to at least partially remove slimes and/or loose particles from the
40 surface. In addition the debris clearance head 47 serves to drive any debris
which is generated by the excising operation forward of the excising vehicle 40
25 such that the debris does not inhibit the movement of the excising vehicle along
the pipeline. If desired the excising function, the washing function and the debris
clearance function of the excising vehicle may be effected in unison or
independently as separate functions. In addition in the event that the amount of
45 debris in the pipeline inhibits the progress of the excising vehicle through the
pipeline it may be necessary to extract the excising vehicle from the pipeline and
50
55

- 15 -

effect the removal of the debris from the pipeline by at least partial utilisation of one or more of the debris removal vehicles as described below.

Once the excising step has been completed or during the excising step it will become necessary to remove from the pipeline the debris which has been generated by the excising step. This is effected by use of at least one of the debris removal vehicles which are shown at Figures 4, 5 and 6.

The debris removal vehicles comprise a primary removal vehicle 50 as shown at Figure 4 which is intended to remove large items of debris from the pipeline, a secondary removal vehicle 60 as shown at Figure 5 which is intended to brush the lower surface of the pipeline to remove smaller items and a tertiary removal vehicle 70 as shown at Figure 6 which enables the collection of fine materials and residual water which has been not collected by the primary and secondary removal vehicles. Each of the removal vehicles is associated with an operator trolley 51, 61 and 71 which are of a similar form to the operator trolley used with the inspection vehicle. Each operator trolley 51, 61 and 71 is able to accommodate an operator and is provided with a hand control whereby the operator is able to effect all of the functions of the respective vehicle. In addition each removal vehicle is associated with a battery pack 52, 62 and 72 respectively which is supported upon its own wheeled chassis and which powers the drive motors for the wheels of the primary, secondary and tertiary removal vehicles 50, 60 and 70 respectively as well as the motors associated with the conveying means (when present) and any other ancillary apparatus.

The primary removal vehicle 50 is provided with a forwardly extending scoop 53 which is supported upon a forwardly extending frame 54 which is pivotally supported from the forward end of the main body of the primary removal vehicle 50. A hydraulic ram or like extension means is provided between the chassis and the frame 54 in order to control the elevation of the scoop 53 from the lower surface of the pipeline. In addition the scoop 53 is associated with a conveyor which comprises an endless belt 55 which extends along the length of the forwardly extending frame and for a portion of the length of the body of the

5 primary removal vehicle 50 to terminate at a hopper 56 provided in the primary
removal vehicle 50. In use the primary removal vehicle is moved along the
10 pipeline with the scoop 53 in close engagement with the lower face of the pipeline
whereby large items of debris are picked up by the scoop and carried to the
5 conveyor whereby they are then conveyed to the debris hopper. The hopper 56
which is provided in the primary removal vehicle 50 is provided with at least one
15 closure on its lower face whereby the closure may be selectively opened to
permit the contents of the hopper to be dumped. This is effected when the
primary removal vehicle 50 is supported upon the tray 11 provided in the gap 10
20 between the two ends of the pipeline 12 whereby the closure is located directly
over the opening 13 provided in the tray in order that the contents of the hopper
are deposited onto the ground below the tray.

25 The secondary removal vehicle 60 as shown at Figure 5 is provided at its forward
end with a brushing unit comprising a brush 63 having a profile corresponding to
15 the profile of the lower portion of the pipe and which by its action is able to deliver
debris from the floor of the pipeline to a hopper 65 provided within the body of the
secondary removal vehicle 60. The secondary removal vehicle 60 is also
30 provided with a vacuum extraction means whereby the smaller debris not
collected by the brush is sucked through a duct 64 to a second hopper 66
35 provided within the body of the secondary removal vehicle. The hoppers 65 and
66 are also provided with at least one closure on their lower face to enable the
contents of the hoppers to be deposited from the hoppers when the secondary
40 removal vehicle is located on the tray 11 located in the gap 10 between two ends
12 of the pipeline.

25 The tertiary removal vehicle 70 as shown at Figure 6 comprises a washing and
vacuum extraction unit whereby the excised portions of the pipe can be finally
45 cleaned. The vehicle comprises a water reservoir 73 which is connected through
a pump 74 to an outlet nozzle 75 which is intended to direct a spray of water into
the lower portion of the pipe. The outlet nozzle 75 is associated with a vacuum
50 30 inlet 76 which is connected to a hopper 77 whereby the water and entrained
debris collecting in the lower portion of the pipe can be picked up and deposited

5 into the hopper 76 supported on the vehicle. The hopper 77 is provided with at least one closure in its lower face whereby the hopper can be opened to enable the contents to be deposited from the hopper when the tertiary removal vehicle is supported upon the tray 11 in the gap 10 between the two ends 12 of the pipe.

5 As a result of the utilisation of the three debris removal vehicles the surface of the pipe can be thoroughly cleaned subsequent to the excising action and in preparation for the application step.

15 The application step comprises the selective application of a fresh lining composition to the locations at which the pre-existing lining has been excised from the pipeline by the excising step. In order to replace the damaged lining an application vehicle of the form as shown as Figure 7 is utilised. The application vehicle comprises an operator trolley 80 which is intended to accommodate an occupant and which has a hand control 81 to facilitate the controlled movement of the application vehicle along the pipeline. In addition the operator trolley 80 is provided with an application means for the application of a lining composition onto the wall of the pipe. The application means can comprise a spray nozzle 82 supported upon on a radial arm 83 which is able to rotate about an longitudinal axis of the pipeline and which can be controlled in its movement and operation by the operator to effect a localised application of the lining composition to the pipeline. Where the application step involves the wholesale application of a lining composition to a large area the application means may comprise a spinner head which is caused to rotate about a longitudinal axis and which has an outlet from which the lining composition is delivered to be thrown centrifugally against the internal face of the pipeline to effect a spray pattern around the inner circumference of the pipeline.

45 The application vehicle also comprises a hopper vehicle 90 which is supported in the pipeline by a set of driven wheels 91 which are associated with drive motors. The hopper vehicle 90 accommodates a hopper for the lining composition which is connected to the application means through a delivery means in the form of an auger and through a pump for the delivery of the lining composition to the

5 application means. The application vehicle is also associated with a battery
vehicle 84 which is supported upon a wheeled chassis 85 and which is towed
10 behind the hopper vehicle 90.

15 The application vehicle is also associated with a delivery vehicle 100 whereby
5 the hopper 93 of the application vehicle can be refilled with the lining
composition. The delivery vehicle 100 is associated with an operator trolley 110
15 which accommodates an occupant who is able to control all of the functions of the
delivery vehicle. In addition the operator trolley 110 is provided with a visual
display unit screen which is associated with a camera and lighting means 103
20 10 provided at the forward end to the vehicle 100 whereby the operator is able to
determine the location of the delivery relative to the application vehicle when
approaching the application vehicle.

25 The delivery vehicle 100 comprises a hopper 104 which is intended
accommodate the lining composition. The hopper 104 is connected to a pump
15 15 through a feed auger 105 which is connected to a delivery pipe 106 which
30 extends forwardly from the delivery such that when the delivery vehicle is in close
abutment with the rearward end of the application vehicle the delivery pipe 106 is
located to enable the lining composition being delivered from the delivery pipe
35 will be deposited into the hopper 93 of the application vehicle.

40 20 The delivery vehicle 100 enables the application vehicle to be used continuously
in applying lining composition to the excised portions of the lining at the locations
at which the lining has been excised without the need to return to the most
adjacent gap 10 to be refilled with lining composition.

45 25 The embodiment according to the invention provides a means whereby the life of
an existing lined pipeline can be extended without the need to effect wholesale
replacement of the pipeline or complete replacement of lining of that pipeline
which may include sound lining. Rather the method according to the embodiment
50 involves the identification of those portions of the pipeline which have suffered

5 significant deterioration, excising of those portions of the lining from the existing lining and then replacement of the excised portion with fresh lining composition.

10 According to a second embodiment of the invention the inspection step and the excising step are effected remotely by the use of the same vehicle. In the case of
5 the second embodiment the camera of the excising vehicle of the first embodiment is used to remotely inspect the state of the lining as the excising
15 vehicle travels along the pipeline. On a portion of the lining being identified as being inadequate the excising nozzle is activated to remove the lining so identified. In the case of the second embodiment the observation by the camera
20 10 may be supplemented by other sensing means to assess the quality of the lining in order to assess its adequacy. In addition the state of the pipeline before and/or after the excising action may be logged at the control station.

25 According to a second embodiment of the invention the removal vehicle may comprise a single vehicle which is able to achieve each of the functions of the
15 primary, secondary and tertiary removal vehicles of the first embodiment.

30 According to a third embodiment of the invention the application vehicle may comprise a single vehicle which incorporates the combined features of the forward and rearward vehicles of the first embodiment.

35 According to a third embodiment the invention is applied to the selective
20 refurbishment of the lining of an underground pipeline whereby the pipeline is exposed at spaced positions to enable a gap of the form described above in
40 relation to the first embodiment to be created in the pipeline at each position and the pipeline to be treated in the manner described above in relation to each of the above embodiments. According to an alternative embodiment openings are
45 25 formed at each position rather than gaps.

Throughout the specification, unless the context requires otherwise, the word
50 "comprise" or variations such as "comprises" or "comprising", will be understood

5

to imply the inclusion of a stated integer or group of integers but not the exclusion of any other integer or group of integers.

10

It should be appreciated that the scope of the present invention need not be limited to the particular scope of the embodiments described above.

15

20

25

30

35

40

45

50

55